

TEST REPORT



Nordforest Hookaroon

OWNER OF TEST CERTIFICATE:

Test no.: 9014

Grube KG Forstgerätestelle
Hützeler Damm 38
DE – 29646 Bispingen

www.grube.de





Test results and evaluations

Grube KG Forstgerätestelle, Hützeler Damm 38,
D-29646 Bispingen

Application field

Lifting of firewood during manual processing with hand tools and when using splitters, occasional chipping of weak knots and wood fiber residues, as well as for universal use with recovery vehicles.

Test item	Test results
Handling	<p>Good force application of the tip with ergonomically favorable hand position and good weight distribution.</p> <p>Safe penetration of the tip in softwood, in hardwood and frozen wood due to the low weight and shape of the hook higher impact energy required</p> <p>Very good grip due to anti-slip surface</p> <p>Handle not replaceable</p>
Durability	Maintenance-free handle, due to the handle texture no detachment of the head from the handle even in case of breakage.

Design

Hook / impact head made of tool steel, curved hollow handle made of glass fibre reinforced plastic with knob and suspension device, handle with anti-slip surface. Cutting edge protection available in silicone or plastic.

Technical specifications

Overall length / handle profile:	625 mm / oval 36 x 25 mm
Overall weight:	810 g
Head	
length:	220 mm
width:	4 mm
Height:	115 mm
Cutting edge angle:	16°

In the field of measurement tolerances, the Hookaroon is still manufactured unchanged.

Published with funding from the Federal Ministry of Food and Agriculture on the basis of a resolution of the German Bundestag and by the Federal State Ministries of Forestry by:



Test committee equipment and tools

**Chairman: Dr. Johannes Windisch,
Regensburg**

Test completion December 2022

Approval until December 2027

First approval August 2019

Responsible test engineer

Rainer Kobow

Rainer.Kobow@kwf-online.de

Practical work with professional users

Kuratorium für Waldarbeit und Forsttechnik e.V.

Spremlinger Straße 1

D - 64823 Groß-Umstadt

Phone: +49 6078/785-15

Fax: +49 6078/785-50

Homepage: www.kwf-online.de