

TEST REPORT



BAHCO large felling lever (Art. no. 1030) various version

Test no: 0777

OWNER OF TEST CERTIFICATE:

SNA Europe (Industrie) AB
Bruggevägen 3
SE - 828 32 EDSBYN
Sweden

www.bahco.com



Test Results and Evaluations



SNA Europe (Industrie) AB, Bruggevägen 3, SE - 828 32 EDSBYN

Application field

Turning of stems and stem parts up to ca. 35 cm.

Felling of hangers in medium wood.

Version	Felling	Freeing of hangers	Turning
Long felling lever 130 cm	≤ 25 cm DBH	≤ 25 cm DBH	≤ 35 cm DBH

Test item	Test result
Handling	Ergonomic, well-formed, non-slip handle. Footplate bites well into wood. Turning hook slidable along the handle.
Durability	Forged footplate, welded to the handle. Material quality and workmanship is good. No damage during test.
Work safety	Only approved for solo worker. Operational limits must be observed.

Design

Footplate and lever forged in high quality stainless steel. Plastic handle fitted to lever. Turning hook loosely attached to lever, fixed to shaft in a holster.

Technical specifications

Lever length	1.300 mm
Angle footplate - lever	20 °
Footplate L x W x T	65 mm x 103 mm x 8 mm
Handle length	260 mm
Profile	15 mm x 35 mm, rectangular profile
Handle profile (plastic)	43 mm x 22 mm, 0-Profile
Overall weight	3.400 g

In the field of measurement tolerances, the BAHCO large felling lever (Art.no. 1030) various versions, is still manufactured unchanged.

Published with funding from the Federal Ministry of Food and Agriculture on the basis of a resolution of the German Bundestag and by the Federal State Ministries of Forestry by:



Test committee equipment and tools
Chairman: Dr. Johannes Windisch,
Regensburg

Test completion **May 2021**
Approval until **May 2026**
First approval **September 1986**
Responsible test engineer
Rainer Kobow
rainer.kobow@kwf-online.de

Practical work with professional users

Kuratorium für Waldarbeit und Forsttechnik e.V.
 Spremberger Straße 1
 D - 64823 Groß-Umstadt
 Phone: +49 6078-785-0
 Fax: +49 6078/785-50
 Homepage: www.kwf-online.de